



tapes  
gloves  
work protection

## technical data sheet

ul flame retardent pvc rubber electrical insulation tape



### description

black flame retardent pvc film backing with high tack rubber adhesive.

**product code:** S88BLU

### specifications

backing  
pvc film

tensile strength  
76.5n/25mm

adhesive  
rubber

elongation  
250%

total thickness  
0.180mm

temp resistance  
130°C

adhesion to steel  
7n/25mm

colours  
blue

standard sizes  
18mm x 20m

custom slit  
n/a

### benefits

flame retardent  
high tack adhesive  
easy unwind

### areas of use

building / construction  
electrical repairs  
electronics



tapes  
gloves  
work protection

## technical data sheet

### conditions of use

for best results apply self adhesive tapes between 15°C and 25°C in a dry environment. application surfaces must be dry and free from dust and particles. do not apply on surfaces treated or contaminated by anti-adhesives. do not use paint containing additives which could reduce the adhesive properties. avoid contact with surfaces containing plasticizers or other chemical agents not compatible with the tape. in cases of rough or irregular surfaces, it is better to use a tape with a higher quantity of adhesive. care must be taken with reference to removability without residue and working conditions of the self adhesive tape.

### tape storage

suggested storage temperature shall range between 15°C and 25°C with maximum relative humidity of 65%. material shall be stored away from heat sources and possible kept in the original package, avoiding light exposure as well. when temperatures are lower than suggested, it is always required to recondition the adhesive tape to normal temperatures before use.

### tape shelf life

self-adhesive tapes technical features are generally not permanent but remain at their best for a minimum of 12 months, if stored according to suggested conditions and avoiding extreme environmental conditions such as quick and sudden temperature changes, extremely high or low temperatures, high levels of humidity, etc.

the information provided is based on our experience and tape industry knowledge. it is given in goodwill but is not intended as a guarantee or warranty. all end users should ensure themselves that the product is suitable for their own particular application before using.

All **selfgard™** and **pomona® products** are trademarks of Pomona Group Ltd and are under license in New Zealand.