


TECHNICAL DATA SHEET

Printable Water Activated Gum Paper

Product Code **GP04BP**



Pomona Group Limited
PO Box 21806, Henderson
Auckland 0650
P 0800 766 662
www.pomona.co.nz



PRODUCT COMPOSITION

| SPECIFICATIONS | |
|-----------------------|--|
| CODE | GP04BP |
| DESCRIPTION | Printable Water Activated Gum Paper |
| FEATURES AND BENEFITS | 100% recyclable and repulpable Sheer slit for high quality finished rolls Tamper evident Strong adhesion Made from natural kraft paper Water activated Good flexibility and superior strength Customised Printing |
| AREAS OF USE | Transport Shipping |
| COLOUR | Natural |
| SIZES AVAILABLE | 36mm x 50m (24 Rolls / Carton) 48mm x 50m (18 Rolls / Carton) 72mm x 50m (12 Rolls / Carton) |
| SLITTING OPTIONS | Custom slit available on request |

| PHYSICAL PROPERTIES | |
|--------------------------|------------------------------------|
| BACKING (LINER) | 80g/m ² Kraft Paper |
| ADHESIVE TYPE | Water Activated - Vegetable Starch |
| MAXIMUM TENSILE (N/25MM) | MD 190 / CD 60 |
| TOTAL THICKNESS (MM) | 0.13 |



The figures above are based off average results from multiple tests, results may vary + or - 5%

Tapes / Gloves / Work Protection

100% New Zealand Owned & Operated

CONDITIONS OF USE

For best results apply self-adhesive tapes between 15°C and 25°C in a dry environment. Application surfaces must be dry and free from dust and particles. Do not apply on surfaces treated or contaminated by anti-adhesives. Avoid contact with surfaces containing plasticizers or other chemical agents not compatible with the tape. Care must be taken regarding removability without residue and working conditions of the self-adhesive tape.

TAPE STORAGE

Ideally, store tape between 4°C and 26°C with a maximum relative humidity between 40% and 50%. Always store away from heat sources, avoiding exposure to light and if possible keep in the original packaging. Rotation of stock is recommended. When temperatures are lower than 15°C, it is highly recommended to recondition the adhesive tape to the average temperature range (4°C to 26°C) before use.

TAPE SHELF LIFE

Self-adhesive tapes technical features are generally not permanent but remain at their best for approximately 12 months, if stored according to suggested conditions and by avoiding extreme environmental conditions such as quick and sudden temperature changes, exposure to UV light and high levels of humidity.

OTHER INFORMATION

All test methods are based on ASTM standards and Pomona's standardised test methods. The information provided above is based on our experience and tape industry knowledge. It is given in goodwill but is not a guarantee or a warranty. All end-users should ensure for themselves that the product is suitable for their particular application before using.

NB: Peak Force Test: based on ASTM 3759/D ASTM 3759/M and Pomona® test methods,
Peel Test: based on ASTM D3330 and Pomona® test methods.

Pomona & Selfgard™ products are registered and under trademark of Pomona Group Ltd & sold exclusively through selected distributors.

For further information on **Pomona** or **Selfgard™** please email sales@pomona.co.nz, phone **0800 0800 766662** or contact your distributor.

Tapes / Gloves / Work Protection
100% New Zealand Owned & Operated